

ONDASIL1 - POLI



STRUCTURE

Silicone hump hoses made of VMQ (Vinyl Methyl Quali) silicone, with polyester reinforcement. Possibility to be supplied with Fluorosilicone liner (FVMQ) or silicone oil resistant, and/or aramidic fibres reinforcements (Nomex®, Kevlar®, etc.)

TEMPERATURE RANGE







-55 °C up to +180°C with peaks to +200 °C

COLOUR

Blue, other on request

APPLICATION

Cooling systems for passenger cars, motorbikes, excavators, industrial veichles, busses and general industrial systems. Turbo-charger and intercooler systems

 Inner diameter (mm)	 Wall thickness (mm)	 Reinforcement number	 Wall thickness tolerance (mm)	 Hardness (Shore A)	 Length (mm)
45	4,5	3	+1 / -0,5	65 - 75	102
51	5	4	+1 / -0,5	65 - 75	102
60	5	4	+1 / -0,5	65 - 75	102
63	5	4	+1 / -0,5	65 - 75	102
70	5	4	+1 / -0,5	65 - 75	102
76	5,5	5	+1 / -0,5	65 - 75	102
80	5,5	5	+1 / -0,5	65 - 75	102
90	5,5	5	+1 / -0,5	65 - 75	102
102	5,5	5	+1 / -0,5	65 - 75	102

