



TFP SP FIBER



MATERIAL

Flexible tube made of a fabric of glass fiber coated self-extinguishing PVC spiral reinforcement steel inserted internally

APPLICATION

Fume extraction, vapor, hot air, civil and naval air conditioning

SELF-EXTINGUISHING

According to UL 94 V-0 class and grade M1 according to NFP 92 503 D/V

TEMPERATURE RANGE







-20 °C to +90 °C with peaks up to 120 °C

AXIAL COMPRESSIBILITY

80%

COLOUR







Grey

|  Inner diameter (mm) |  Weight (g/m) |  Bending radius (mm) |  Working pressure (mbar) |  Vacuum (mbar) |  Length (m) |
|---|--|---|---|---|--|
| 40 | 130 | 23 | 550 | 100 | 10 |
| 50 | 160 | 25 | 500 | 100 | 10 |
| 60 | 190 | 30 | 450 | 90 | 10 |
| 65 | 205 | 33 | 400 | 90 | 10 |
| 70 | 220 | 35 | 400 | 80 | 10 |
| 76 | 225 | 38 | 350 | 75 | 10 |
| 80 | 245 | 40 | 350 | 70 | 10 |
| 90 | 275 | 45 | 300 | 65 | 10 |
| 100 | 290 | 50 | 300 | 60 | 10 |
| 110 | 310 | 55 | 250 | 55 | 10 |
| 120 | 330 | 60 | 250 | 50 | 10 |
| 125 | 340 | 63 | 200 | 45 | 10 |





TUBIFLESSIBILI

|  Inner diameter (mm) |  Weight (g/m) |  Bending radius (mm) |  Working pressure (mbar) |  Vacuum (mbar) |  Length (m) |
|---|--|---|---|---|--|
| 130 | 355 | 65 | 200 | 40 | 10 |
| 140 | 445 | 70 | 150 | 35 | 10 |
| 150 | 480 | 75 | 150 | 25 | 10 |
| 160 | 505 | 80 | 100 | 20 | 10 |
| 180 | 510 | 90 | 100 | 15 | 10 |
| 200 | 570 | 100 | 80 | 10 | 10 |
| 225 | 630 | 113 | 60 | 5 | 10 |
| 250 | 810 | 125 | 50 | 5 | 10 |
| 275 | 875 | 138 | 40 | 5 | 10 |
| 300 | 950 | 150 | 30 | 2 | 10 |
| 320 | 1000 | 160 | 25 | 2 | 10 |
| 350 | 1260 | 170 | 10 | 1 | 10 |
| 400 | 1440 | 200 | 10 | 1 | 10 |

