

TFP SP PUR 0.4



MATERIAL

Hose in polyurethane ester spiral reinforcement harmonic galvanized steel or copper. The thickness of 0.40 mm makes the tube very lightweight and flexible. Excellent mechanical properties, resistant to abrasion, cold, aging and to many chemicals. Absence of PVC and halogen

TEMPERATURE RANGE







From -40 °C to +90 °C.

COLOUR

Transparent

APPLICATION







Suitable aspirations and blowing dust, fumes, sawdust, shavings minor, etc

 Inner diameter (mm)	 Weight (g/m)	 Bending radius (mm)	 Working pressure (mbar)	 Vacuum (mbar)	 Length (m)
50	210	25	400	40	20
60	265	30	380	40	20
70	335	35	345	35	20
76	360	38	305	35	20
80	365	40	285	30	20
90	405	45	240	30	20
100	450	50	210	25	20
110	495	55	210	25	20
120	535	60	200	20	20
125	555	63	200	20	20





TUBIFLESSIBILI

 Inner diameter (mm)	 Weight (g/m)	 Bending radius (mm)	 Working pressure (mbar)	 Vacuum (mbar)	 Length (m)
130	580	65	190	20	20
140	700	70	160	15	20
150	750	75	120	15	20
160	795	80	105	15	20
180	890	90	95	10	20
200	990	100	95	10	20
225	1115	113	85	10	10
250	1235	125	50	10	10
275	1840	139	30	10	10
300	1990	150	30	10	10

