

TFP SP PVC



MATERIAL







Flexible PVC hose reinforced with PVC helix wire

TEMPERATURE RANGE

-10 °C up to +60 °C

APPLICATION

Suction and delivery hose, suitable for notabrasive or fatty generic media and foodstuffs requiring simulating liquid as type A-B-C, widely used for industrial, agricultural, marine sector. Non toxic PVC, suitable for foodstuffs contact.

|  Internal diameter (mm) |  Weight (g/m) |  Maximal pressure (bar) |  Suction pressure (bar) |  Bending radius (mm) |  Roll length (m) |
|--|--|--|--|---|---|
| 14 | 150 | 6 | 1 | 55 | 55 |
| 15 | 155 | 6 | 1 | 70 | 70 |
| 16 | 175 | 6 | 1 | 80 | 80 |
| 18 | 190 | 6 | 1 | 90 | 90 |
| 20 | 210 | 5 | 1 | 100 | 100 |
| 25 | 280 | 5 | 1 | 125 | 125 |
| 30 | 330 | 5 | 1 | 150 | 150 |
| 32 | 350 | 4,5 | 1 | 160 | 160 |
| 35 | 400 | 4,5 | 1 | 175 | 175 |
| 38 | 430 | 4,5 | 1 | 185 | 185 |
| 40 | 480 | 4 | 1 | 200 | 200 |
| 50 | 760 | 4 | 1 | 250 | 250 |
| 60 | 1000 | 4 | 1 | 320 | 320 |
| 80 | 1500 | 4 | 1 | 480 | 480 |
| 90 | 1800 | 4 | 1 | 550 | 550 |
| 100 | 2200 | 3 | 1 | 620 | 620 |

