



TUBIFLESSIBILI

TUBOSIL TRECCIATO R/B



MATERIAL

VMQ (Vinyl Methyl Quality) silicone hoses, polyester textile reinforcements

APPLICATION

Connections between radiators and engines, for passenger cars, lorries, industrial vehicles, power generators, for conveying of cooling liquids and antifreeze

TEMPERATURE RANGE

-60 °C up to +180°C with +200 °C peak

COLOUR






Blue external, red internal

STANDARD LENGTHS

25 meters, others on request

CHARACTERISTICS

Meets and exceeds SAE J 20 R1 class A

 Inner diameter (mm)	 Wall thickness (mm)	 Working pressure (bar)	 Burst pressure (bar)	 Roll length (m)
6	4,0	5,5	17,5	25
8	4,0	5,5	17,5	25
10	4,0	5,5	17,5	25
13	4,0	5,5	17,5	25
16	4,0	5,5	17,5	25
19	4,0	4,5	14	25
22	5,0	4,0	12	25
25	5,0	4,0	12	25
30	5,5	4,0	12	25
32	5,5	4,0	12	25

Tubi Flessibili S.r.l. - Tel: +39 0131238971 - Email: info@tubiflessibili.net

According to ISO 1307

Above technical data are referring to applications at a room temperature (+20°C)

Copyright © TUBI FLESSIBILI S.r.l. - All rights reserved. The texts and images are property of Tubi Flessibili S.r.l. Even partial reproduction of the catalog is prohibited.

