

TURBOSIL NMX



STRUCTURE

Hump hose with steel rings made of VMQ (Vinyl Methyl Quality) silicone, with aramidic or poliester fiber reinforcements. Possibility to be supplied with Fluorosilicone liner (FVMQ) or silicone oil resistant fibers reinforcements (Nomex[®], Kevlar[®], etc.)

TEMPERATURE RANGE








-55 °C / + 230 °C with + 260 °C peaks

COLOUR

Red iron oxide, other on request

APPLICATION

Engine/turbocharger, turbocharger/intercooler systems for endothermic engines for passenger cars, industrial vehicles, busses, construction equipments, current generators etc.

 Internal diameter (mm)	 Total length (mm)	 Humps	 Rings	 Reinforcements	 Wall thickness tolerance (mm)	 Hardness (Shore A)
32	160	2	3	4	+1 / -0,5	65 - 75
42	160	2	3	4	+1 / -0,5	65 - 75
45	160	2	3	4	+1 / -0,5	65 - 75
50	165	2	0	4	+1 / -0,5	65 - 75
50	165	1	2	4	+1 / -0,5	65 - 75
50	165	2	3	4	+1 / -0,5	65 - 75
60	130	2	3	4	+1 / -0,5	65 - 75
60	200	4	5	4	+1 / -0,5	65 - 75
63	95	1	0	4	+1 / -0,5	65 - 75
63	100	1	2	4	+1 / -0,5	65 - 75
63	120	2	1	4	+1 / -0,5	65 - 75
63	160	2	3	4	+1 / -0,5	65 - 75
65	120	2	3	4	+1 / -0,5	65 - 75

Tubi Flessibili S.r.l. - Tel: +39 0131238971 - Email: info@tubiflessibili.net








According to ISO 1307
Above technical data are referring to applications at a room temperature (+20°C)

Copyright © TUBI FLESSIBILI S.r.l. - All rights reserved. The texts and images are property of Tubi Flessibili S.r.l.
Even partial reproduction of the catalog is prohibited.





TUBIFLESSIBILI

 Internal diameter (mm)	 Total length (mm)	 Humps	 Rings	 Reinforcements	 Wall thickness tolerance (mm)	 Hardness (Shore A)
70	76	1	0	4	+1 / -0,5	65 - 75
70	350	10	11	4	+1 / -0,5	65 - 75
75	120	1	2	4	+1 / -0,5	65 - 75
76	160	2	3	4	+1 / -0,5	65 - 75
76	200	4	5	4	+1 / -0,5	65 - 75
80	135	2	3	4	+1 / -0,5	65 - 75
85	150	2	3	4	+1 / -0,5	65 - 75
89	110	1	2	4	+1 / -0,5	65 - 75
89	140	3	2	4	+1 / -0,5	65 - 75
89	165	1	2	4	+1 / -0,5	65 - 75
89	190	2	3	4	+1 / -0,5	65 - 75
89	210	4	5	4	+1 / -0,5	65 - 75
90	290	7	8	4	+1 / -0,5	65 - 75
100	100	2	3	4	+1 / -0,5	65 - 75
100	160	0	0	5	+1 / -0,5	65 - 75
102	220	3	4	4	+1 / -0,5	65 - 75
114	210	4	5	4	+1 / -0,5	65 - 75
128	202	3	3	5	+1 / -0,5	65 - 75
128	210	4	5	4	+1 / -0,5	65 - 75

Tubi Flessibili S.r.l. - Tel: +39 0131238971 - Email: info@tubiflessibili.net

According to ISO 1307
Above technical data are referring to applications at a room temperature (+20°C)

Copyright © TUBI FLESSIBILI S.r.l. - All rights reserved. The texts and images are property of Tubi Flessibili S.r.l.
Even partial reproduction of the catalog is prohibited.

